### **Distributed by Tri-State Equipment Company Inc.**

sales@tsoverheadcrane.com www.tsoverheadcrane.com

Tel: (314) 869-7200



# **New Demag DC-Com chain hoist**



## Longer service life drives added value

Our Demag DC-Com chain hoists have always been the cost-effective solution for standard applications. We have now made them even more attractive by increasing their performance. The DC-Com model offers significantly more value with twice the service life and a 50% increase in duty factor (for size 2 and higher).

DC-Com hoists are designed for normal standard requirements. Thanks to their new FEM classification and duty factor, DC-Com hoists are now even more cost-effective. Their extremely rugged aluminum housing contains proven Demag hoist engineering for reliable operation. DC-Com units are very user-friendly and feature high standards of safety and reliability. They can be installed and put into operation quickly and easily.

#### SIMPLE COMMISSIONING

- Plug & Lift and Plug & Drive all electrical connections are plug-in design
- Simply attach the hoist to the trolley using the folding suspension bracket
- U 11 to U 34 trolleys can be quickly and easily adjusted to variable flange widths

Load capacity		Chain hoist	Reeving	Group of mechanisms	Lifting speed		Lift	Continuous Duty Factor	16' Lift
[lbs]	[kg]	Туре		FEM/ISO	[FPM]	[m/min]	[ft.]	[%]	(for H5) [lbs]
175	80	DC-Com 1	1/1	4m/M7	32/8	9.6/2.4	16' or 26' <sup>1)</sup>	60 (40/20)	49 / 21
220/275	100/125			3m/M6					
350	160	DC-Com 2		3m/M6	24/6	7.2/1.8		60 (40/20)	
440/550	200/250			2m/M5					
695	315	DC-Com 5		3m/M6	24/6	7.2/1.8		60 (40/20)	62 / 27
880/1,100	400/500			2m/M5					
1,390	630	DC-Com 10		3m/M6	16/4	4.8/1.2		60 (40/20)	106 / 47
1,765/2,200	800/1,000			2m/M5					
2,755	1,250	DC-Com 10	2/1	3m/M6	16/4	4.8/1.2		60 (40/20)	143 / 63
3,525/4,400	1,600/2,000			2m/M5					

1) Longer hook paths on request





## Your benefits with the Demag DC-Com chain hoist

### **RELIABLE DEMAG QUALITY**

- 24V contactor control
- High level of safety thanks to the brake arranged in front of the slipping clutch
- Reliable operation from -4 to +113 °F (-20 °C to +45 °C) without any reduction in the duty factor (maximum of up to 140 °F / 60 °C)
- Two lifting speeds as standard with smooth starting and braking
- Maintenance monitoring thanks to a standard elapsed operating time counter and IDAPSY diagnostics interface
- Outstanding surface protection thanks to highquality powder-coating
- IP 55 enclosure
- The entire chain drive can be quickly replaced without having to remove the motor or gear parts
- Gearbox maintenance-free for up to 10 years

The Demag DC-Pro chain hoist product range offers additional functions and options – also in the form of the variable-speed DCS-Pro and DCM-Pro Manulift models.

### **ERGONOMIC HANDLING**

- The length of the control cable can be adjusted without the need for any wiring, therefore the control pendant can always be in the right working position
- Fatigue-free operation thanks to the ergonomically optimized DSC and DSE 10-C control pendants
- Single-fall design for simple load handling (for units up to 2,200 lbs / 1,000 kg)
- Service-friendly
- Service Cover allows direct and quick access to:
  - Key plug-and-socket electrical connections
  - Control pendant height adjustment
  - Chain lubrication port

### TROLLEYS AND ELECTRIC DRIVES

Besides operation with the KBK crane construction kit, DC-Com chain hoists can also be used on I-beam and Patented Track Crane and Monorails. The push-travel trolleys are designed for smooth, low rolling resistance travel. Electric travel drives can also be added to the trolley for heavier loads. These travel drives feature adjustable, two-speed travel as well as smooth starting and stopping.





Demag Cranes & Components Corp. 29201 Aurora Road

### Distributed by Tri-State Equipment Company Inc.

sales@tsoverheadcrane.com www.tsoverheadcrane.com

Tel: (314) 869-7200