



OZXR500DAV - 500lb XR Series Davit Crane Specifications

Manufacturer Info:
OZ Lifting Products
5455 W. 6th St.
PO Box 845
Winona MN, 55987

Section 1

2.1 Davit Crane

Section 2

Manufacturer: davit crane shall be of domestic manufacture, as manufactured by OZ Lifting Products, OZXR500DAV.

Load Capacity: davit crane shall have a load capacity of 500lbs at all boom positions.

Design Factor: davit crane shall be designed with an ultimate design factor exceeding 2:1 for all components, in all boom positions.

Proof Testing: davit crane shall be individually proof tested by manufacturer to 125% of rated load.

Hook Reach: davit crane shall have a hook reach of **41.66** inches when the boom is **in the lowest position**, measured from mast centerline to hook centerline.

Height Adjustments: davit crane boom shall have four points of height adjustment, the first at **16 degrees** followed by **26, 36, 46** degrees.

Boom Sheave: davit crane shall have a sheave at the end of the boom that the cable shall pass over.

Height Clearance: when used with the socket base, davit crane shall have a minimum clearance of **26.88** inches between the mounting surface and underside of boom. **When** used with pedestal base, davit crane shall have a minimum clearance of **40.88** inches between the mounting surface and underside of boom.

Rotation: davit crane shall freely rotate 360 degrees in mounting base.

Pins: davit crane components shall be assembled using clevis style pins made from RHoS compliant zinc

plated corrosion resistant alloy steel.

Portability: davit crane shall have the ability to be completely assembled and dis-assembled without tools, with a total weight not to exceed **60lbs** (exclusive of winch and cable).

Winch mounting: davit crane shall have a dedicated winch mounting surface located on the top of the boom to accept either a manual or electric winch.

ID Tag: davit crane shall be labeled with a metal identification plate permanently attached, marked in such a way as to be free of corrosion or marking degradation, and to include manufacturer's name, serial number, model number, load capacity, contact information, and other pertinent information.

2.2 Bases

Manufacturer: davit crane bases shall be of domestic manufacture, as manufactured by OZ Lifting Products, OZSOC3, OZPED3, and OZWALL3.

Base Style: davit crane shall utilize purpose built socket, pedestal, and wall mount bases, not those of universal design. Part numbers OZSOC3, OZPED3, and OZWALL3.

Usage: bases shall allow davit crane mast to be installed and removed easily, with no tools.

Bearing surfaces: base shall have a self-lubricating nylon bearing sleeve to support mast rotation while also having a pin at the bottom of the base to positively engage the base of the mast.

2.3 Finish

Materials: davit crane, bases, and pins shall be domestically made from steel meeting ASTM standards.

Finish: davit crane, bases, and pins shall be RHoS compliant corrosion resistant zinc plated and/or powder coated.

2.4 Winches

Manual Winch: winch shall be of the brake winch type, utilizing a Weston style load holding brake, a quick-disconnect removable handle, bronze bearings, and available drill driven option.

Winch Capacity: load capacity of the winch to be appropriately sized to match that of the davit crane.

Finish: winch shall have all steel parts zinc plated.

Cable Attachment: winch shall facilitate cable attachment via either a standard cable anchor clamp, or a ball swaged cable end fitting.



OZXR1000DAV - 1000lb XR Series Davit Crane Specifications

Manufacturer Info:
OZ Lifting Products
5455 W. 6th St.
PO Box 845
Winona MN, 55987

Section 1

2.1 Davit Crane

Section 2

Manufacturer: davit crane shall be of domestic manufacture, as manufactured by OZ Lifting Products, OZXR1000DAV.

Load Capacity: davit crane shall have a load capacity of 1,000lbs at all boom positions.

Design Factor: davit crane shall be designed with an ultimate design factor exceeding 2:1 for all components, in all boom positions.

Proof Testing: davit crane shall be individually proof tested by manufacturer to 125% of rated load.

Hook Reach: davit crane shall have a hook reach of **41.66** inches when the boom is **in the lowest position**, measured from mast centerline to hook centerline.

Height Adjustments: davit crane boom shall have four points of height adjustment, the first at **16 degrees** followed by **26, 36, 46** degrees.

Boom Sheave: davit crane shall have a sheave at the end of the boom that the cable shall pass over.

Height Clearance: when used with the socket base, davit crane shall have a minimum clearance of **26.63** inches between the mounting surface and underside of boom. when used with pedestal base, davit crane shall have a minimum clearance of **39.88** inches between the mounting surface and underside of boom.

Rotation: davit crane shall freely rotate 360 degrees in mounting base.

Pins: davit crane components shall be assembled using clevis style pins made from RHoS compliant

corrosion resistant zinc plated alloy steel.

Portability: davit crane shall have the ability to be completely assembled and dis-assembled without tools, with a total weight not to exceed **95lbs** (exclusive of winch and cable).

Winch mounting: davit crane shall have a dedicated winch mounting surface located on the top of the boom to accept either a manual or electric winch.

ID Tag: davit crane shall be labeled with a metal identification plate permanently attached, marked in such a way as to be free of corrosion or marking degradation, and to include manufacturer's name, serial number, model number, load capacity, contact information, and other pertinent information.

2.2 Bases

Manufacturer: davit crane bases shall be of domestic manufacture, as manufactured by OZ Lifting Products, **OZSOC1-TP, OZPED1-TP, and OZWALL1-TP**.

Base Style: davit crane shall utilize purpose built socket, pedestal, and wall mount bases, not those of universal design. Part numbers **OZSOC1-TP, OZPED1-TP, and OZWALL1-TP**.

Usage: bases shall allow davit crane mast to be installed and removed easily, with no tools.

Bearing surfaces: base shall have a self-lubricating nylon bearing sleeve to support mast rotation while also having a pin at the bottom of the base to positively engage the base of the mast.

2.3 Finish

Materials: davit crane, bases, and pins shall be domestically made from steel meeting ASTM standards.

Finish: davit crane, bases, and pins shall be RHoS compliant corrosion resistant zinc plated and/or powder coated.

2.4 Winches

Manual Winch: winch shall be of the brake winch type, utilizing a Weston style load holding brake, a quick-disconnect removable handle, bronze bearings, and available drill driven option.

Winch Capacity: load capacity of the winch to be appropriately sized to match that of the davit crane.

Finish: winch shall have all metal parts zinc plated.

Cable Attachment: winch shall facilitate cable attachment via either a standard cable anchor clamp, or a ball swaged cable end fitting.